SOME ADVANCES ON T-SPLINE PARAMETERIZATION BASED ON THE MECCANO METHOD

López J.I.¹, Brovka M.¹, Escobar J.M.¹, Cascón J.M.² and Montenegro R.^{1,*}

¹University Institute for Intelligent Systems and Numerical Applications in Engineering (SIANI), University of Las Palmas de Gran Canaria (ULPGC),
Campus Universitario de Tafira, 35017 Las Palmas de Gran Canaria, Spain,
http://www.dca.iusiani.ulpgc.es/proyecto2012-2014,
jilopez@siani.es, mbrovka@siani.es, jmescobar@siani.es, rafa@dma.ulpgc.es

²Department of Economics and Economic History, Faculty of Economics and Management, University of Salamanca, Spain, http://campus.usal.es/~sinumcc, casbar@usal.es

Key words: T-spline parameterization, Simultaneous T-mesh untangling and smoothing, Meccano method, Isogeometric analysis

We have recently introduced a new strategy, based on the meccano method [1, 2], to construct a T-spline parameterization of 2D and 3D geometries for the application of isogeometric analysis [3, 4]. The proposed method only demands a boundary representation of the geometry as input data. The algorithm obtains, as a result, high quality parametric transformation between the objects and the parametric domain, i.e. the meccano. The key of the method lies in defining an isomorphic transformation between the parametric and physical T-mesh finding the optimal position of the interior nodes, once the meccano boundary nodes are mapped to the boundary of the physical domain. A procedure for simultaneous untangling and smoothing of T-meshes is applied to reach this objective. Bivariate or trivariate T-spline representations are calculated by imposing the interpolation conditions on points sited both on the interior and on the boundary of the geometry. The proposed method also permits modeling of objects with embedded geometries that can be used for domains composed of several materials. In this paper we present several advances of the proposed technique. Its effectiveness is shown in several examples. Some results of the application of isogeometric analysis are also presented.

REFERENCES

[1] R. Montenegro, J.M. Cascón, J.M. Escobar, E. Rodríguez, G. Montero. An automatic strategy for adaptive tetrahedral mesh generation. *Applied Numerical Mathematics*, Vol. **58**, 2203-2217, 2009. http://dx.doi.org/10.1016/j.apnum.2008.12.010

- [2] J.M. Cascón, E. Rodríguez, J.M. Escobar, R. Montenegro. Comparison of the meccano method with standard mesh generation techniques. *Engineering with Computers*, 1–14, on-line 2013. http://dx.doi.org/10.1007/s00366-013-0338-6
- [3] J.M. Escobar, J.M. Cascón, E. Rodríguez, R. Montenegro. A new approach to solid modeling with trivariate T-splines based on mesh optimization. *Computer Methods in Applied Mechanics and Engineering*, Vol. **200**, 3210–3222, 2011. http://dx.doi.org/10.1016/j.cma.2011.07.004
- [4] M. Brovka, J.I. López, J.M. Escobar, J.M. Cascón, R. Montenegro. A new method for T-spline parameterization of complex 2D geometries. *Engineering with Computers*, on-line 2013. http://dx.doi.org/10.1007/s00366-013-0336-8